



Features

QHÁN•^Á@#@#}åÁsd{Ásd&@#^&c'¦^Á&@¶•È

l ÈÁY [[å^}Ás[φÊÁ}ã ~^Á@[∖Ás^•ã}ÊÉnæ•^ÁgÁs•œa∮ÊÁã]|^Ása}åÁ,¦æ&œ&æHÊÁφč ĭãrãc∧Ása}åÁs^æĕcã×jÈ

ÍÉÁV@^Áç[|ˇ{^Á&æ)Áa^Áæåbŏ•c^åÁs@;[ੱ*@ÁÓÚÁ,^ç[¦\Áa¦[æå&æ•cÁ•[~çæb^Á;¦Á;[àāp^Á&|an}}dÈ

Î ĐÁUˇ]][¦ơ Á^æḥĒcāṭ ^Á,^c; [¦\Á,|æêàæ&\ĐÁ&@°åˇ|^åÁ,|æêàæ&\ĐÁæ)åÁa^ā;*Á,æ*^åĐÁæ)åÁ&æ)Á^&^ãç^Ár^•ơ{ Áơ¦{ā;æḥÁ à¦[æå&æ•ơ•È

ÏĖÀÒ~~ã,]^åÁ,ãc@ÁœÁœedåÁ∧•∧oÁà~cd;}Áq;Á∧æqã∧Á;}∧Ë8|ã&λÁ∧•d;¦ææã;}Áq;Á&q;}æã;}È

ìÈÒ``ā]]^åÁ, ão@ŠÒÖÁ;cæc`•Áājå å&æq[¦Á[¦Á;æ•^Ád;[`à|^•@[[cāj*È

$$\begin{split} J \dot{E} \dot{U}^*]] [| \dot{O} \dot{A} \wedge \{ [e^* \dot{A}_1 \} | \ddot{a}_1 \wedge \dot{A}_1 | * | a e^* \dot{A}_1 + \dot{A}_2 + \dot{A}_1 | [* | a e^* \dot{A}_1 | A a e^* \dot{A}_1 | [* | a e^* \dot{A}_1 | A a e^* \dot{A}_1 | [* | a e^* \dot{A}_1 | A a e^* \dot{A}_1 | A a e^* \dot{A}_2 | A$$

FFEAN+ \vec{a} * \vec{A} ^ | \vec{E} ^ \vec{c} ^ | \vec{C} | \vec{A} | \vec{C} |

Page 1 www.TciTech.com.tr



Specification

Model	TCI-515W
Frequency Response	20Hz-20KHz
SNR	80dB
Dynamic Range	80dB
THD	0.005%
Sampling Rate	8K-48KHz
Network Transmission Rate	100Mbps
Audio Format	16-bit CD quality
Power Supply	~220V/50Hz
Dimension	167*140*140mm
Net Weight	1.7KG
Gross Weight	2.0KG

Page 2 www.TciTech.com.tr