



Features

- 1.Black aluminum alloy panel, high-end and elegant;
- 2.Silicone buttons, soft and durable, comfortable to the touch, and highly plastic.
- 3.Using CLASS D amplifier circuit, low heat generation and high efficiency;
- 4.6 signal inputs (2 lines, 3 microphones, **1 EMC for emergency alarm**);
- 5.Two phantom power microphones, switches are controlled separately, can drive phantom power microphones;
- 6.RS232 control, Bluetooth, USB, TF card interface, automatic playback function when powered on;
- 7.LED 7-digit digital tube display;
8. With infrared remote control operation function;
9. Independent volume adjustment of each channel;
10. Independent adjustment of treble and bass;
- 11.The power supply adopts high-performance switching power supply circuit, low heat generation and high efficiency;
12. It has perfect output short circuit protection, DC protection, high temperature protection and other functions

Specification

Model	TCI-60CMT	TCI-120CMT	TCI-240CMT
Rated Power	60W	120W	240W
Speaker Output Mode	Low impedance:4-16 Ohms		
	Voltage line:70V & 100V		
Compatible Media	USB, TF, Bluetooth, AUX IN		
Microphone Input	MIC1/MIC2: 600 ohms(Ω) 10 mv, MIC1/MIC2 (balanced), MIC1 front (unbalanced)		
Line Input	AUX1/AUX2: 10K Ohms(Ω) 300 mv, unbalanced		
Auxiliary Output:	0.775V (0 dB)		
Frequency Response	60Hz~18KHz (± 3 dB)		
Distortion THD	<0.5% at 1KHz, 1/3 rated output power		
SNR	AUX:>80 dB, MIC:>65dB		
Tone	Bass: 100 Hz (± 10 dB), Treble: 10KHz (± 10 dB)		
Power Supply	AC100V~AC240V $\pm 10\%$ 50-60Hz		
Power Consumption	90W	160W	290W
Dimension	63(H) $\times$ 215(W) $\times$ 285(D) mm		
Packing Size	135(H) $\times$ 290(W) $\times$ 325(D) mm		
Net Weight	1.8KG	2.5KG	3KG
Gross Weight	2.5KG	3.2KG	3.5KG