



Specifications

Model	TCI-P2300	TCI-P2400	TCI-P2500	TCI-P2600	TCI-P2800	TCI-P21000	TCI-P21200	TCI-P21600
Rated Power@8Ohm	2*300W	2*400W	2*500W	2*600W	2*800W	2*1000W	2*1200W	2*1600W
Output Mode	4-8 ohms(Ω)							
Intermodulation distortion 60HZ/7HZ 4: 1	< 0.04%							
Damping coefficient	Single channel operation, 8Ω load 400HZ (≥300)							
Frequency Response	20-20KHZ <±0.1dB							
THD	< 0.5% at 1kHz							
S/N 8Ω load A-weighted	>100dB	>90dB	>90dB	>90dB	>90dB	>90dB	>90dB	>90dB
Conversion rate	>Single channel operation, 8Ω load 10HZ square wave (≥40V/us)							
Input sensitivity	<3 dB, from level without signal to be loaded fully							
Input impedance	Normal operating conditions, 1HZ 20Kohms balanced input, 10Kohms							
Input interface	XLR female socket							
Output interface	OhmXLR							
Protection mode	Short circuit, overheating, overload, undervoltage, output DC							
Min load impedance single channel operation	>4Ω							
Ambient temperature	Working temperature: -10℃-40℃, storage temperature: -25℃-80℃							
Power Supply	185-240V 50/60HZ							
Power Consumption	1100W	1200W	1500W	1800W	2300W	2900W	3300W	4200W
Dimension	485×410×89mm			485×440×89mm				
Packing Size	550×500×189mm			550×580×189mm				
N.W	10kg	11kg	12kg	13kg	15kg	17kg	18kg	20kg
G.W	12kg	13kg	14kg	15kg	17kg	19kg	20kg	22kg