



Features

1. Built-in music streaming media including USB player, FM tuner and Bt receiver.
2. 70/100-volt and 4~16 ohms(Ω) output loads.
3. Two microphone (MIC1 & MIC2) jacks, MIC2 supports 48V Phantom Power with switch ON/OFF.
4. MIC1 has "VOICE PRIORITY" over the other inputs except of the alarm input
5. EMC input has priority over the other inputs.
6. SMT circuit boards with highly stable performance.
7. High-definition display for the working status of playing program.
8. Individual volume controller for inputs, and master volume controller for all.
9. BASS and TREBLE tone controllers.
10. Power supply AC100-240V and DC24V.
11. Protection provided for output short circuit, overload, high temperature, peak current limiters.

Specification

Model	TCI-60DT	TCI-120DT
Rated Power	60W	120W
Speaker Output Mode	Low impedance:4-16 ohms (Ω)	
	Voltage line:70V & 100V	
Compatible Media	USB,BT,FM,Aux In	
Playable Formats	MP3,WMA,WAV,FLAC,APE	
BT Name	TCI-60DT/TCI-120DT	
BT Frequency	2402~2480 MHz	
BT E.I.R.P	2 dBm	
FM Tuner Frequency	87.50~107.50 MHz	
Frequency Response	60 Hz ~ 15k Hz (± 3 dB)	
T.H.D	<1% at 1kHz,1/3 rated power	
S/N	≥ 75 dB	
Tone Control	BASS:100 Hz (± 10 dB) , TREBLE:10k Hz (± 10 dB)	
Protection	Short circuit,overload,high temperature	
AC Power Supply	AC100V~230V / 50Hz, 0.33A	
AC Fuse	T3.15A	
DC Power Supply	DC24V, 3.13A	
Power Cord	(3 $\times$ 0.75 mm ²) $\times$ 1.5M	
Dimension	71(H) $\times$ 300(W) $\times$ 191(D) mm	
Carton Size	120(H) $\times$ 350(W) $\times$ 255(D) mm	
Net Weight	4.90kg	5.50kg
Gross Weight	5.60kg	6.10kg