



Features

1. 5 MIC inputs, 3 AUX inputs, 2 EMC input, 4 AUX outputs.
2. Individual volume controller for MIC & AUX inputs.
3. MASTER volume controller ,BASS and TREBLE tone controller.
4. EMC1,2 have priority over all inputs except MIC1.
5. Built-in SIREN circuitry with pushbutton on front panel for an orderly emergency evacuation of people and conducting a fire or an emergency drill manually.
6. Connecting Alarm Panel for emergency broadcasting automatically.
7. Built-in CHIME circuitry with pushbutton on front panel for attracting listeners' attention prior to speaking.
8. 4 signal outputs for connecting 4 units of power amplifiers.

Specification

Model	TCI-10P
MIC Input	MIC 1,2,3,4,5: 18mV/600 ohms, Unbalanced
AUX Input	AUX 1,2,3: 200mV/10k ohms, Unbalanced
EMC Input	EMC 1,2: 1.5V/10k ohms, Unbalanced
Tone	BASS:±10dB at 100Hz,TREBLE:±10dB at 10KHz
Frequency Response	20Hz - 20KHz
S/N Ratio	MIC 1,2: 70dB; AUX 1,2,3: 80dB
THD	Less than 1%
Muting Function	attenuation,EMC1,2 overrides all inputs except MIC1
LED Indicators	POWER
Protection	AC fuse
Power Requirements	AC220V±10%,50/60Hz
Power Consumption	50W
Dimensions (W×D×H)	483(W)×366(D)×89(H)mm
Weight	7.5Kg